



City III LED Recessed Gimble CCT 92mm Cut Out Downlight in White

SKU: 170764

$62.95 (inc GST)

Details

Direct light with precision while maintaining a clean ceiling aesthetic with the **City III Gimble LED Downlight in White**. Its adjustable design lets you aim illumination towards artwork, work surfaces or architectural features, while the white finish sits quietly within lighter ceilings.
This 11.5W recessed gimbal downlight delivers up to 1050 lumens and fits a 92mm cut-out. Select Warm White (3000K), Cool White (4000K) or Daylight (5000K) using the built-in switch. The **Scene Change at the Wall Switch** functionality offers convenient control from the wall switch. Dimmable performance provides flexible control of brightness and ambience.
Ideal for layered lighting in living rooms, hallways and interior feature zones, the City III combines directional performance with a streamlined contemporary form and a 5-year warranty. The City III Gimble range is also available in Black, Brushed Chrome and Brass.

Specifications

SKU	170764
Colour/Finish	White
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
Ip Rating	IP20
Globe Type	Integrated LED
Globe Quantity	0
Wattage Max	11.5W



Kelvins	3000K/4000K/5000K
Lumens	1050
CRI	>90
Efficacy	91.3
Beam Angle	60 degrees
Field Angle	80 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	92
Ic (Insulation Contact) Rated	IC-4
Gimble Angle	65 degrees
Colour Temperature	Warm White/Cool White/Day Light
Voltage	240V
Surge Protection	500V
Double Insulated	false
Sdcm	=6 (3000K/5000K) =7 (4000K)
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	25 degrees
Warranty	5 years
Brand	Lucci
Style	Modern
Down Lighting Type	COB LED
Downlight Technology	Adjustable Control – Scene Change via Toggle or Wall Switch

Dimensions

Height (mm)	63
Width (mm)	100
Weight (kg)	0.4
Box Height (mm)	116
Box Depth (mm)	114
Box Width (mm)	114
Cable Length	500mm