

# MFL Fleming LED 15 Light Recessed Warm White 402mm X 38mm Cut Out Downlight in Black

SKU: 170883

**Details**

MFL Fleming 15 light downlight is dimmable, and for the best dimming range, use with the Lucci LEDlux SKU# 290998 dimmer and adjust the variable resistor at minimum and maximum dimming positions on the dimmer during the installation. These dimmers are also compatible: Buster + Punch DIM-002 DIGINET LED Smart MEDM, Clipsal 31E2RUDM, 32E450TM, 32E450UDM, 31E2PUDM and 32ELEDM, HPM: Cat. 400T The use of a dimmer with this downlight that has not been tested to be compatible may void your warranty. Product specifications are from the latest shipment of these products as LED production is constantly improving. Current stock may have different specifications to what is stated on the website.

**Specifications**

| | |
|---|---|
| SKU | 170883 |
| Colour/Finish | Black |
| Dimmable | Yes |
| Recommended Dimmers | Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018. |
| Ip Rating | IP20 |
| Globe Type | Integrated LED |
| Globe Quantity | 0 |
| Wattage Max | 30W |
| Kelvins | 3000K |
| Lumens | 2000 |
| CRI | >92 |
| Efficacy | 66.7 |
| Beam Angle | 30 degrees |

| | |
|---|---|
| Field Angle | 50 degrees |
| Average Rated Life | 25,000 hours |
| Cut Out Size (mm) | 402 x 38 |
| Ic (Insulation Contact) Rated | IC-4 |
| Colour Temperature | Warm White |
| Material | Aluminium |
| Voltage | 240V |
| Sdcm | 6 |
| Operating Temperature | -20 degrees to 40 degrees |
| Ambient Temperature | 25 degrees |
| Warranty | 3 years |
| Brand | MFL |
| Style | Modern |

**Dimensions**

| | |
|---|---|
| Height (mm) | 50 |
| Width (mm) | 45 |
| Depth (mm) | 412 |
| Weight (kg) | 0.9 |
| Box Height (mm) | 75 |
| Box Depth (mm) | 460 |
| Box Width (mm) | 85 |
| Cable Length | 1250mm |