



Slipstream 142cm DC Fan with Light in White

SKU: 213308

$389.00 (inc GST)

Details

The Slipstream ceiling fan range pairs a clean, contemporary design with powerful airflow performance, making it an ideal choice for larger living areas, bedrooms and covered outdoor spaces. Available in black or white, the range features four streamlined ABS blades and a 142 cm blade span that meets Queensland NCC requirements for larger rooms while maintaining a simple, versatile aesthetic.
Powered by an energy-efficient DC motor, the Slipstream delivers strong airflow with quiet operation and six selectable speeds. The integrated light includes a replaceable GX53 globe with selectable colour temperatures and smooth dimming via the included rechargeable remote. Coastal-rated construction extends its suitability to covered outdoor environments, while Wi-Fi adaptability offers the option for smart control integration. Combining proven performance, practical functionality and modern styling, the Slipstream range is designed to provide reliable comfort throughout the home.
Available in black or white

DC Motor - Efficient, Cost Saving, and Quiet

The most energy-efficient ceiling fans on the market right now are DC, or direct current, fans. The key to their improved airflow and low energy consumption is their motor, which also helps you save money on your electricity bill. Since the motor is small and light, DC ceiling fans have sleek designs that fit better in your interiors and cost just one cent an hour to run. Additionally, they are silent in operation, making them ideal for private spaces in your house like the bedroom. You have a lot of versatility with the speed settings of DC fans, which range from a light breeze to an extremely intense airflow.

Remote Control

6-speed rechargeable remote control. *USB-C cord and charger are not included. For instructions on how to pair the remote, please follow the steps in this video: Remote Pairing

Smart Compatible

Insert the Lucci Connect Wi-Fi Module (sold separately - 216180) into the receiver to activate smart functionalities. Once paired with the Lucci Connect app, you can turn your fan on/off, adjust

its speed, set timers, and even create schedules based on the temperature outside.

Optional Light

Versatility to use light with included GX53 globe, or use included cap to cover the socket for a no light option. The GX53 globe included has colour changing technology (warm-white, cool-white and daylight), and can be smooth dimmed via the remote control.

Coastal Rating

Suitable for indoor, alfresco, and coastal areas provided the fan is fully undercover, protected from water, wind, and dust, with a minimum of 1 wall.

Recommended Room Size

For rooms between 3m x 3m and 4m x 4m, we recommend a fan between 122cm and 142cm.

2-Year In-Home + 7-Year Motor Replacement Warranty

We provide a 2-year in-home warranty and a 7-year motor replacement warranty on all hard-wired Lucci or Fanaway fans that were purchased from 1st October 2022. Plus, if you have your fan purchased or installed by a Beacon Lighting Trade member, we'll extend your in-home warranty on the nominated Lucci or Fanaway fan for an extra 1 year, which means you'll enjoy a 3-year in-home warranty.

Click Here for range specification sheet

Specifications

SKU	213308
Colour/Finish	White
Airflow	247m3/min
Fan Speed	6 speed remote control
Remote Control	Remote Included
Location	Coastal Use
No. Of Blades	4
Fan Blade Size	56in / 142cm
Blade Pitch	12.3 degrees
Reversible	Yes
Globe Included	true
Colour Temperature	Warm White, Cool White, Day Light
Kelvins	3000K/4000K/5000K
Lumens	1350
Dimmable	Via Remote
Wattage Max	12W
Fanlight Available	Included

Globe Quantity	1
Globe Type	GX53
Efficacy	112.5
Voltage	240V
Current	DC
Poles	12
Fan Motor Wattage	40W
Decibels	0
Rpm	0
Ceiling Pitch	6 degrees
Standard Ceiling Drop	330mm
Brand	Lucci Air
Style	Modern
Warranty	2-year in-home + 7-year motor warranty
Extension Rod	210575, 210422

Dimensions

Height (mm)	340
Width (mm)	1410
Weight (kg)	5.2
Box Height (mm)	268
Box Depth (mm)	725
Box Width (mm)	255