



Vivid LED Recessed Colour Switch 90mm Cut Out Downlight in White

SKU: 170571

Details

The LEdlux Vivid colour switch downlight enable you to choose which colour tempertaure of light you would like between 3000K Warm White - 4000K Cool White and 5000K Daylight. This light is IP44 rated only after it is fully installed and this must be maintained during installation. however the driver and back of the light is IP20 rated. This downlight is compatible with the following dimmers:
lumex Load Smart LT1D450ls;
DIGINET LED Smart MEDM;
Clipsal 31E2RUDM, 32E450TM, 32E450UDM, 31E2PUDM and 32ELEDM;
HPM: Cat. 4007;
LUCCI LEDlux SKU#290998, SKU #290997
It is highly recommended to use the LUCCI LEDlux dimmers for best dimming range.

Specifications

SKU	170571
Colour/Finish	White
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
Ip Rating	IP44
Globe Type	Integrated LED
Globe Quantity	0
Wattage Max	10.5W
Kelvins	3000K/4000K/5000K
Lumens	1000
CRI	>80



Efficacy	95.2
Beam Angle	110 degrees
Field Angle	160 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	90
Ic (Insulation Contact) Rated	IC-4
Colour Temperature	Warm White/Cool White/Day Light
Material	Aluminium
Voltage	240V
Surge Protection	500V
Double Insulated	false
Sdcm	=6 (3000K/5000K) =7 (4000K)
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	50 degrees
Warranty	5 years
Brand	Lucci
Style	Modern
Down Lighting Type	SMD LED
Downlight Technology	Scene Change via Toggle

Dimensions

Height (mm)	45
Width (mm)	104
Weight (kg)	0.3
Box Height (mm)	97
Box Depth (mm)	114
Box Width (mm)	114
Cable Length	300mm