

LIVERPOOL 2LT EXTERIOR FLOOD LIGHT

SKU# 240256, 240258

Rated Voltage 220-240V~ 50Hz

Thank you for purchasing this quality Lucci product. To ensure correct function and safety, please read and follow all instructions carefully before assembly, installation and use of this product. Please keep instructions for future reference.

Warranty

- This light fitting is covered by a 12 month warranty. The warranty is from date of purchase, not the date of installation.
- If the fitting is not assembled and installed by a licensed electrician the warranty will be void.
- Please retain proof of purchase and evidence of installation by a licensed electrician for any warranty claims.
- Warranty will be void if there is any damage due to improper usage or modification to the fitting.
- Failure to comply with the instructions in this manual may increase the risk of damage or injury and will void warranty.

Installation Requirements

- This fitting must be assembled and installed by a licensed electrician.
- All wiring and installation of the light fitting must adhere to local and national wiring rules. eg. AS/NZS 3000:2007/Amendment 2:2012 Electrical installations.
- This fitting is a Class I product and must be earthed.
- This fitting is rated IP44, this must be maintained during wiring and installation.
- Do not exceed the maximum wattage rating.
- Select a suitable location for installation:
 - The mounting point must be able to support 2 times the weight of the fitting.
 - A clearance of 0.5m must be kept between the globe and the nearest wall or object etc.
 - This fitting is protected against water penetration to IP44 standards, which is splashing water from any direction.
 - Only to be installed outside arms reach.
- Take care not to pull any electrical wires during unpacking as this may damage the connection.
- Lay out all the components on a smooth surface and make sure there are no components missing before assembling. If parts are missing, return the complete product to the place of purchase for inspection or replacement.
- Check whether the fitting has been damaged during transport. Do not operate/install any product which appears damaged in any way. Return the complete product to the place of purchase for inspection, repair or replacement.
- Ensure power to the circuit you are working on has been switched OFF before commencing any electrical work.

Installation Directions

1. Remove all packaging material from the product and be careful not to throw away accessories that may be hidden within the packaging material.
2. Use the fitting as a template to mark the screw positions on the wall. Drill holes into the wall and put the plastic anchors into the holes. Ensure the plastic anchors used are suitable for the mounting surface (Fig. 1)
3. Remove the cover from the terminal box and connect the mains supply wire to the terminal block. (Fig. 2)
Ensure the wires are secure and no bare wires are exposed.


Mains Supply Wire

Earth – Yellow/Green 

Neutral – Blue or Black

Live – Brown or Red

Fitting Wire

Yellow/Green or 

Blue or N


Brown or L

4. Install the fitting onto the wall with the screws provided. Ensure the screws used are suitable for the mounting surface. Take note of the directional label. (Fig. 3)

NOTE: It is recommended that a non-corrosive bead of silicone be applied before installation onto the wall ensuring that no water can run down into the cabling.

5. Install globes (not included) into the lamp holders. Do not exceed the maximum wattage rating. Check and ensure there is a seal between the globe, gasket and fitting. (Fig. 4)

6. Check that all parts are secured tightly. Switch on the fitting to test and enjoy your new lighting product.



Safety Tips

- Always ensure the power is OFF and the fitting has cooled down before performing any maintenance, cleaning, changing the globe or making any adjustment to the fitting.
- To avoid injury or damage to the fitting, ensure that power leads and screws are secure before connecting the power.
- Ensure that the fitting does not come in contact with corrosive chemicals/solvents or abrasive cleaners etc.
- To clean, wipe with a soft damp cloth. Do NOT soak or immerse the product in water or other liquids.

Specifications

SKU #	240256	240258
Finish/Material	304 Stainless Steel	316 Stainless Steel
Rated Voltage	220-240V~ 50Hz	
Rated Wattage	300W Max. (2x Max 150W PAR38 globe)	
Lamp Holder	ES / E27	
IP Rating	IP44	
Weight	0.8kg	
Dimensions	H:115mm W:230mm E:125mm	