



## LEDlux Vivid Colour Switch Downlight in White

### DESCRIPTION

The LEDlux Vivid colour switch downlight enable you to choose which colour tempertaure of light you would like between 3000K Warm White - 4000K Cool White and 5000K Daylight. This light is IP44 rated only after it is fully installed and this must be maintained during installation. however the driver and back of the light is IP20 rated. This downlight is compatible with the following dimmers:

lumex Load Smart LT1D450Is;

DIGINET LED Smart MEDM;

Clipsal 31E2RUDM, 32E450TM, 32E450UDM, 31E2PUDM and 32ELEDM;

HPM: Cat. 4007;

LUCCI LEDlux SKU#290998, SKU #290997

It is highly recommended to use the LUCCI LEDlux dimmers for best dimming range.

### SPECIFICATIONS

SKU	170571
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
IP Rating	44
Globe Type	Integrated LED
Globe Quantity	1
Wattage Max	10W
Colour Temperature	Warm White/Cool White/Day Light
Kelvins	3000K/4000K/5000K
Lumens	850
CRI	>80
Efficacy	85
Beam Angle	110 degrees
Field Angle	160 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	90
IC (Insulation Contact) Rated	IC-4
Material	Aluminium
Voltage	240V
Double Insulated	Yes
Sdcm	=6 (3000K/5000K) =7 (4000K)
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	50 degrees
Height (mm)	45
Weight (kg)	0.3
Brand	Lucci LEDlux
Depth (mm)	0
Globe Included	Yes
Product Type	Lighting



Width (mm)	104
Cable Length	300mm
Colour/Finish	White
Style	Modern

[Click here for installation instruction](#)

