



LEDlux Express Mini LED Dimmable White Downlight in Warm White

\$31.95

DESCRIPTION

This downlight has integrated LED's in the fitting. This fitting is dimmable and has been tested with Lucci LEDlux SKU 290998 dimmer, Clipsal 32E450TM, Clipsal 31E2RUDM and Clipsal 32E450UDM dimmers only. The use of a LED dimmer such as the Lucci LEDlux SKU 290998 dimmer is highly recommended. For the best dimming range, use with the Lucci LEDlux SKU 290998 dimmer and adjust the variable resistor at minimum and maximum dimming positions on the dimmer during installation. The use of non-recommended dimmers may damage your LED light fitting and will void the warranty. This fitting has an insulating ceiling type IC rating. Building insulation material can safely be exposed continuously to temperatures up to 90°C may abut and cover the luminaire.

SPECIFICATIONS

| | |
|-------------------------------|--|
| SKU | 170575 |
| Dimmable | Yes |
| Recommended Dimmers | Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018. |
| IP Rating | 44 |
| Globe Type | Integrated LED |
| Globe Quantity | 1 |
| Wattage Max | 12W |
| Colour Temperature | Warm White |
| Kelvins | 3000K |
| Lumens | 900 |
| CRI | >80 |
| Efficacy | 75 |
| Beam Angle | 95 degrees |
| Field Angle | 150 degrees |
| Average Rated Life | 25,000 hours |
| Cut Out Size (mm) | 92 |
| IC (Insulation Contact) Rated | IC-4 |
| Material | Aluminium |
| Voltage | 240V |
| Double Insulated | Yes |
| Sdcm | <6 |
| Operating Temperature | -20 degrees to 40 degrees |
| Ambient Temperature | 25 degrees |
| Height (mm) | 49 |
| Weight (kg) | 0.3 |
| Brand | Lucci LEDlux |
| Depth (mm) | 0 |
| Globe Included | Yes |
| Product Type | Lighting |
| Width (mm) | 120 |
| Cable Length | 500mm |
| Colour/Finish | White |
| Style | Modern |





[Click here for installation instruction](#)



support@beaconlighting.com.au



03 8561 1599

Date printed 28 April 2024