



## Express Mini LED Recessed Warm White 92mm Cut Out Downlight in White

### DESCRIPTION

This downlight has integrated LED's in the fitting. This fitting is dimmable and has been tested with Lucci LEDlux SKU 290998 dimmer, Clipsal 32E450TM, Clipsal 31E2RUDM and Clipsal 32E450UDM dimmers only. The use of a LED dimmer such as the Lucci LEDlux SKU 290998 dimmer is highly recommended. For the best dimming range, use with the Lucci LEDlux SKU 290998 dimmer and adjust the variable resistor at minimum and maximum dimming positions on the dimmer during installation. The use of non-recommended dimmers may damage your LED light fitting and will void the warranty. This fitting has an insulating ceiling type IC rating. Building insulation material can safely be exposed continuously to temperatures up to 90°C may abut and cover the luminaire.

### SPECIFICATIONS

SKU	170575
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
IP Rating	44
Globe Type	Integrated LED
Globe Quantity	0
Wattage Max	12W
Colour Temperature	Warm White
Kelvins	3000K
Lumens	900
CRI	>80
Efficacy	75
Beam Angle	95 degrees
Field Angle	150 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	92
IC (Insulation Contact) Rated	IC-4
Material	Aluminium
Voltage	240V
Double Insulated	Yes
Sdcm	<6
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	25 degrees
Height (mm)	49
Weight (kg)	0.3
Brand	Lucci LEDlux
Depth (mm)	0
Globe Included	No
Product Type	Lighting
Width (mm)	120
Cable Length	500mm
Colour/Finish	White
Style	Modern

[Click here for installation instruction](#)