



Transition Duel LED Recessed Fixed 74mm Cut Out Downlight in White

\$49.95

DESCRIPTION

This LED downlight is suitable for indoor or outdoor use, provided that it is installed under cover or under eaves. It is IP44 rated. It also has CCT, and you select the colour temperature you require via the switch on the back of the downlight during installation. This fitting is dimmable, For the best dimming range, use with the Lucci LEDlux SKU# 290998 dimmer and adjust the variable resistor at minimum and maximum dimming positions on the dimmer during the installation. This downlight is also compatible with these dimmers: BUSTER+ PUNCH DIM-002 LUMEX Load Smart LT1D450LS; DIGINET LED Smart MEDM; Clipsal 32EPUDM, 32E450UDM, 32E450TM, 31E2RUDM and 32ELEDM; HPM: Cat. 400T The use of non-compatible dimmers may damage your LED downlight and will void your warranty. Product specifications are from the latest shipment of these products as LED production is constantly improving. Current stock may have different specifications to what is stated on the website.

SPECIFICATIONS

SKU	170890
Dimmable	Yes
Recommended Dimmers	Lucci LEDlux SKU# 290998, 290997, 299043, 290989, 290992, 290993, 290994. Buster + Punch SKU# 299098, 299099, 299100 299101. Artisan SKU#197015, 197016, 197017, 197018.
IP Rating	44
Globe Type	Integrated LED
Globe Quantity	0
Wattage Max	10W
Colour Temperature	Warm White/Cool White/Day Light
Kelvins	3000K/4000K/5000K
Lumens	800
CRI	>85
Efficacy	80
Beam Angle	70 degrees
Field Angle	105 degrees
Average Rated Life	25,000 hours
Cut Out Size (mm)	74
IC (Insulation Contact) Rated	IC-4
Material	Aluminium
Voltage	240V
Double Insulated	Yes
Sdcm	=6 (3000K/5000K) =7 (4000K)
Operating Temperature	-20 degrees to 40 degrees
Ambient Temperature	50 degrees
Height (mm)	88
Weight (kg)	0.3
Brand	Lucci LEDlux
Depth (mm)	0
Globe Included	No
Product Type	Lighting
Width (mm)	84
Cable Length	300mm



Colour/Finish White
Style Modern

[Click here for installation instruction](#)