



LEDlux Wimberly LED Exterior Wall Bracket With Sensor in Black

\$299.00

DESCRIPTION

Taking its design from the South Hamptons aesthetic, but with a modernist twist. The Wimberly is architecturally crafted with clean lines, and minimalist detailing. The LED panel at the top of the fitting provides exceptional light that reflects beautifully against the delicate glass panels. The LEDlux Wimberly LED exterior wall bracket with integrated LED is IP54 rated. With it's included sensor, The ideal mounting height for the fitting is between 1.5m to 2.5m above the detection area. The detection area is approximately maximum 10 metres away at an angle of 120° wide. This may vary depending on the mounting height and location. This sensor does have a override function.

Product specifications are from the latest shipment of these products as LED production is constantly improving. Current stock may have different specifications to what is stated on the website.

SPECIFICATIONS

SKU	240810
IP Rating	54
Globe Type	Integrated LED
Globe Quantity	1
Wattage Max	13W
Colour Temperature	Warm White
Kelvins	3000K
Lumens	600
CRI	>80
Efficacy	46.2
Material	Aluminium
Voltage	240V
Double Insulated	No
Height (mm)	380
Weight (kg)	2.3
Brand	Lucci LEDlux
Depth (mm)	170
Globe Included	Yes
Product Type	Lighting
Width (mm)	120
Colour/Finish	Black
Location	Alfresco/Indoor Use
Style	Modern
Room Type	Alfresco, Outdoor
Outdoor Lighting Type	Alfresco Lighting, House Lighting

